

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

21 APR 2005

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/037685 A2

(51) International Patent Classification⁷: B65G
(21) International Application Number: PCT/US2003/033356
(22) International Filing Date: 21 October 2003 (21.10.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
60/420,012 21 October 2002 (21.10.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicants and
(72) Inventors: ULSH, Larry, P. [US/US]; 119 Wayfaring Drive, Winchester, VA 22602 (US). ETHERINGTON, Michael [GB/US]; 297 Hunters Ridge Road, Winchester, VA 22602 (US).


Published:

— without international search report and to be republished upon receipt of that report

(74) Agent: LAMBERT, Dennis, H.; Dennis H. Lambert & Associates, 7000 View Park Drive, Burke, VA 22015 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MODULAR CONVEYOR BELT WITH UNIQUE LINK CAPTURE MEANS



(57) Abstract: A flexible conveyor belt (10) has a plurality of transverse rods (11) on which a plurality of links are mounted for rotational and longitudinal movement on the rods. The links include edge links (12a, 12b) at opposite edges of the belt and link modules (13a, 13b and 15) positioned between the edge links. The rods have radially enlarged heads or buttons (16) on their ends, and the edge links have a cavity (29) for receiving the head, and an undercut shoulder (36) against which the head abuts to retain the edge link at the end of the rod. The link modules have a leading end (41) and a trailing end (42), and the trailing end of at least one module (15) has slotted openings (47, 44) to enable the trailing end to be detachably connected to an associated rod. Disengagement of the detachable end of the link module from a rod provides more space on the rod so that the edge link can be slid on the rod to extend the end of the rod outwardly of the edge link to enable a head to be formed on the end of the rod without damaging the adjacent link.

WO 2004/037685 A2